

# NL668-757S-01 LTE Module

## Perfect Wireless Experience

V1.0

## NL668-757S-01 LTE Module Technical Specifications

### Product Feature

- LTE FDD: Band 1/3/5/8
- LTE TDD: Band 38/39/40/41
- WCDMA: Band 1/8
- TD-SCDMA Band 34/39
- EVDO/CDMA1X : BC0
- GSM/GPRS/EDGE: 900/1800MHz
- LCC 32x29x2.4mm
- Operating Temperature: -40°C~+85°C
- Storage Temperature: -40°C~+85°C
- Operating Voltage: 3.3V~4.3V typical 3.8V
- **AT Command Set:** 3GPP TS 27.007 and 27.005, and proprietary FIBOCOM AT commands
- **TX Power**
  - GSM900: 32.5 dBm±1.5dB
  - DCS1800: 29.5dBm±1.5dB
  - WCDMA: 23.5dBm±1.5dB
  - TD-SCDMA: 23.0dBm±1.5dB
  - EVDO: 23.0dBm±1.5dB
  - CDMA1X: 24.0dBm±1.5dB
  - LTE FDD: 23.0dBm±1.5dB
  - LTE TDD: 23.0dBm±1.5dB

### Data

- LTE FDD:75Mbps DL/50Mbps UL
- LTE TDD:65Mbps DL/35Mbps UL
- UMTS: 384 kbps DL/384 kbps UL
- HSPA/HSPA+: 42Mbps DL/5.76Mbps UL
- TD-SCDMA: 4.2Mbps DL/2.2Mbps UL
- EVDO RevA: 3.1Mbps DL/1.8Mbps UL
- CDMA1X: 307.2kbps DL/307.2kbps UL
- EDGE: 296Kbps DL/236.8Kbps UL
- GPRS: 107Kbps DL/85.6Kbps UL

### Function

- MUX: Basic Mode
- SMS: MO/MT Text and PDU modes
- TCP/FTP/UDP
- DFOTA/FOAT
- PPP

### Interface

- SIM Card: 1.8V/3.0V
- USB 2.0
- UART
- GPIO
- System Indicator
- Clock\*
- EINT
- Main Ant

### Driver

- Linux/Android/Windows

*\* Under development*

### Approval

- CCC/SRRC/NAL
- RoHS

Copyright © Fibocom Wireless Inc. | Subject to changes in technology, design and availability | E-mail : market@fibocom.com | Tel : +86 755-2673 3555